AMENIDED

APPLICATION FOR PERMISSION TO CHANGE POINT OF DIVERSION, MANNER OF USE AND PLACE OF USE OF THE PUBLIC WATERS OF THE STATE OF NEVADA HERETOFORE APPROPRIATED

AUG 8 1974

	SEP 2 0 1974 urned to applicant for correction. NOV 1 9 1974 under 28588
ori	rected application filed. NOV 1 9 1374 Map filed NOV 1 9 1974 under 28588
The	applicant E. R. P., Inc.
	P.O. BOX 884 of Reno Street and No. or P.O. Box No. City or Town
	Nevada 89504 , hereby make application for permission to change the State and Zip Code No.
	Point of Diversion and Place of Use of a Portion
of w	vater heretofore appropriated under Permit 26116
	(Identify existing right by Permit, Certificate, Proof or Claim Nos. If Decreed, give title of Decree and identify right in Decree.)
1	The source of water is Underground
٠.	The source of water is Underground Name of stream, lake or other source.
2.	The amount of water to be changed 2.0 cfs Second feet, acre feet.
	The water to be used for Quasi-municipal and Domestic If for stock state number and kind of animals.
	If for stock state number and kind of animals.
5.	The water is to be diverted at the following point. NW SE Section 33 T.21N., R.19E.,
	M.D.B.& M. or at a point from which the E ¹ / ₄ cor. of said Sec. 33 Describe as being within a 40-acre subdivision of public survey and by course and distance to a section corner. If on unsurveyed land, it should be bears N. 87°28'46" 2043.67 feet distant stated.
6.	The existing point of diversion is located within SW NE Section 33 T.21N., R.19E.,
	M.D.B.& M. or at a point from which the E ¹ / ₄ Cor of said Sec 33 bear If point of diversion is not changed, do not answer.
	S. 60°54'19" E., 3003.74 feet distant
7.	Proposed place of use Por SW4 NE4, W2 NW4 SE4, SW4 SE4, SE4 SE4 a portion of Describe by legal subdivisions. If for irrigation state number of acres to be irrigated. SE4 SW4; a portion of NE4SW4 a portion of NW4 SW4, Portion of
	NW1 NE1 Section 33, T.21N., R.19E., M.D.M.
8.	Existing place of use SW14 NE14, W12 NW14 SE14, SW14 SE14, SE14 SE14, a portion of
	Describe by legal subdivisions. If presently used for irrigation, state number of acres irrigated. SE 4 SW4, a portion of NE 5 SW4, a portion of NW4 SW4, portion of
	Section_33, T.21N., R.19E., M.D.B.& M.
9.	Use will be from January 1 to December 31 of each year. Day and Month Day and Month
0.	Use has been from January 1 to December 31 of each year. Day and Month Day and Month
1.	
	specifications of your diversion or storage works.)Drilling.well:construct.water.tank, State manner in which water is to be diverted, whether by dam or other works,
	pressure system and water lines. whether through pipes, ditches, flumes, or other conduits.

14. Estimated time required to complete the application of water to benefic	We will be a second of the second
15. Remarks: For use other than irrigation or stock watering, state number	But the grant of the second of the second
	Take by pool and to the basis of the basis o
Water is to be for same.	
	<u> </u>
Compared Cv/bs 1k/jw Applicant E.	R. P., Inc.
ByS/Jc	ohn W. Millard
APPROVAL OF STATE E	NGINEER
This is to certify that I have examined the foregoing application, and	do hereby grant the same, subject to
following limitations and conditions:	
This permit to change the point of diver	-
of a portion of the waters of an underground	source as heretofore
granted under Permit 26116 is issued subject	to the terms and condi-
tions imposed in said Permit 26116 and with the	he understanding that no
other rights on the source will be affected by	
herein. The well shall be equipped with a 2-	inch opening and a
totalizing meter must be installed and maintage	ined in the discharge
To the state of th	Thea in the arbenarye
pipeline near the point of diversion and accur	rate measurements must
pipeline near the point of diversion and accur be kept of water placed to beneficial use. T	rate measurements must he totalizing meter
pipeline near the point of diversion and accur be kept of water placed to beneficial use. T	rate measurements must he totalizing meter
pipeline near the point of diversion and accurate be kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the	rate measurements must he totalizing meter begins or before the well is flowing, a
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to pre-	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the walve must be installed and maintained to presist located within an area designated by the S	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all times.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes.
pipeline near the point of diversion and accu- be kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to pre- is located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the combined dut	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the combined dut	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined shall be limited to the amount which the amount of water to be changed shall be limited to the amount which	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined shall not exceed 446.6 annum. The amount of water to be changed shall be limited to the amount which to exceed. 2.0 cubic feet per second	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and and a but not to exceed
pipeline near the point of diversion and accumbe kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined shall be limited to the amount which to exceed. 2.0 cubic feet per second 446.6 million gallons annually.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and a decorate to exceed to the total measurement.
pipeline near the point of diversion and accumbe kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined shall be limited to the amount which to exceed. 2.0 cubic feet per second 446.6 million gallons annually.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and a decorate to exceed to the total measurement.
pipeline near the point of diversion and accumbe kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined shall be limited to the amount which to exceed. 2.0 cubic feet per second 446.6 million gallons annually. Actual construction work shall begin on or before.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and med. but not to exceed August 3, 1975
pipeline near the point of diversion and accumbe kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Stone of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the same and same as a second shall not exceed 446.6 annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per second 446.6 million gallons annually. Actual construction work shall begin on or before the same and the same and the same annually. Proof of commencement of work shall be filed before the same annual shall be filed befo	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and and but not to exceed August 3, 1975 September 3, 1979
pipeline near the point of diversion and accumbe kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per second 446.6 million gallons annually. Actual construction work shall begin on or before the proof of commencement of work shall be filed before the completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work must be prosecuted with reasonable diligence and be completed on or work mu	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and med. but not to exceed August 3, 1975 September 3, 1975 or before August 3, 1975
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per secondary. Actual construction work shall begin on or before. Proof of commencement of work shall be filed before. Work must be prosecuted with reasonable diligence and be completed on or Proof of completion of work shall be filed before.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and measurement to exceed August 3, 1975 September 3, 1975 September 3, 1975 September 3, 1975
pipeline near the point of diversion and accurbe kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under to 28592, 28588 and 28944 shall not exceed 446.6 annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per second 446.6 million gallons annually. Actual construction work shall begin on or before. Proof of commencement of work shall be filed before. Work must be prosecuted with reasonable diligence and be completed on or Proof of completion of work shall be filed before. Application of water to beneficial use shall be made on or before.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and measurement to exceed August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the 28592, 28588 and 28944 shall not exceed 446.6 annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per second 446.6 million gallons annually. Actual construction work shall begin on or before. Proof of commencement of work shall be filed before. Work must be prosecuted with reasonable diligence and be completed on or Proof of completion of work shall be filed before. Application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before.	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and re nd , but not to exceed August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water proof of Completion of Work is filed. If the valve must be installed and maintained to presis located within an area designated by the sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the 28592, 28588 and 28944 shall not exceed 446.6 annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per secondary. Actual construction work shall begin on or before cubic feet per secondary. Proof of commencement of work shall be filed before and be completed on one of the application of water to beneficial use shall be filed on or before cubic feet proof of the application of water to beneficial use shall be filed on or before cubic feet proof of the application of water to beneficial use shall be filed on or before cubic feet proof of the application of water to beneficial use shall be filed on or before cubic feet proof of the application of water to beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of beneficial use shall be filed on or before cubic feet proof of proof of beneficial use shall be filed on or before cubic feet proof of proof of beneficial use shall	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and re nd , but not to exceed August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to previse located within an area designated by the Stones 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the samount. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per secondary. Actual construction work shall begin on or before. Proof of commencement of work shall be filed before. Work must be prosecuted with reasonable diligence and be completed on on the proof of completion of work shall be filed before. Application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Note that the water is any use of the water is any use of the samount water is beneficial use shall be filed on or before. Note that the water is any use of the water	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and r defined and source August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976 By I ROLAND D. WESTERGARD
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to preis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the sannum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per secondada and the sannum and all times and the sannum and the sannum. Actual construction work shall begin on or before. Proof of commencement of work shall be filed before. Work must be prosecuted with reasonable diligence and be completed on or Proof of completion of work shall be filed before. Application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Commencement of work filed 1975 IN TESTIMONY WHEREO State Engineer of Nevac	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per a can be applied to beneficial use, and a hd but not to exceed August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976 F, I ROLAND D. WESTERGARD da, have hereunto set my hand and the seal
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to preis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the session of the water herein granted at any and all time. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per secondary. Actual construction work shall begin on or before. Work must be prosecuted with reasonable diligence and be completed on one proof of completion of work shall be filed before. Application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Commencement of work filed 1975 IN TESTIMONY WHEREO State Engineer of Nevac my office, this 320 my o	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per can be applied to beneficial use, and r defined and source August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976 By I ROLAND D. WESTERGARD
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to preis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the second 446.6 annum. The amount of water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per second 446.6 million gallons annually. Actual construction work shall begin on or before. Proof of completion of work shall be filed before. Work must be prosecuted with reasonable diligence and be completed on one of the application of work shall be filed before. Proof of the application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Commencement of work filed 1975 Note Engineer of Nevac my office, this 1975	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per a can be applied to beneficial use, and a hd but not to exceed August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976 F, I ROLAND D. WESTERGARD da, have hereunto set my hand and the seal
pipeline near the point of diversion and accube kept of water placed to beneficial use. The must be installed before any use of the water Proof of Completion of Work is filed. If the valve must be installed and maintained to preis located within an area designated by the Sto NRS 534.030. The State retains the right of the water herein granted at any and all time. The total combined duty of water under the total combined duty of water under the session of the water to be changed shall be limited to the amount which to exceed 2.0 cubic feet per secondary. Actual construction work shall begin on or before. Work must be prosecuted with reasonable diligence and be completed on on the proof of completion of work shall be filed before. Application of water to beneficial use shall be filed on or before. Proof of the application of water to beneficial use shall be filed on or before. Commencement of work filed. Completion of wor	rate measurements must he totalizing meter begins or before the well is flowing, a vent waste. This source tate Engineer pursuant to regulate the use mes. his permit and Permits million gallons per a can be applied to beneficial use, and a hd but not to exceed August 3, 1975 September 3, 1975 September 3, 1975 June 3, 1976 July 3, 1976 F, I ROLAND D. WESTERGARD da, have hereunto set my hand and the seal